



FEATURES

- Ultra-compact, low-profile design in neutral finish
- Energy-efficient LED technology
- EZ snap-out chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

ILLUMINATION

- Ultra-bright, energy efficient long-lasting Red or Green LED

ELECTRICAL

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance-free, rechargeable NiCd battery (EM model)
- Internal solid-state transfer switch automatically connects the internal battery to LED Board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

HOUSING

- Injection-molded engineering-grade, V-0 flame retardant, high-impact thermoplastic in white or black finish
- Curved face, rounded corner design

MOUNTING

- Universal surface mount, wall or ceiling, with EZ-snap thermo-plastic mounting canopy, which snaps into place making installation quick & easy.

LISTINGS AND WARRANTIES

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: **LSXS-2- R-W-EM**

MODEL	# OF FACES	LETTER COLOR	HOUSING COLOR	BATTERY
LSXS	1 - Single Face 2 - Universal Single Double	R - Red G - Green	W - White B - Black	BLANK - AC Only EM - NiCad Battery

NOTE: Product specifications subject to change without notice. Updated 08.2017